

# blueplanet 15.0 + 20.0 TL3

Transformerless, three-phase string inverters.



## The all-rounders among inverters.

High flexibility for demanding system designs and string configurations

Manifold safety functions

Installation-friendly connection area, user-friendly operation

Numerous standard interfaces for extensive communication options

Internal storage of log data, no separate data logger required

OD+ version against salt corrosion in coastal areas

## Technical Data

DC input data	15.0 TL3	20.0 TL3
Max. recommended PV generator	18 000 W	24 000 W
MPP range	420 – 800 V	515 – 800 V
Operating range	200 – 950 V	200 – 950 V
Rated DC voltage / start voltage	673 / 250 V	673 / 250 V
Max. no-load voltage	1 000 V	1 000 V
Max. input current	2 x 20 A	2 x 20 A
Max. short circuit current $I_{sc\ max}$	2 x 32 A	2 x 32 A
Number of MPP tracker	2	2
Connection per tracker	2	2
Max. input power per tracker	15 000 W	15 000 W
AC output data		
Rated output	15 000 VA	20 000 VA
Max. power	15 600 VA	20 800 VA
Line voltage	240 V / 415 V (3 / N / PE) 230 V / 400 V (3 / N / PE) 220 V / 380 V (3 / N / PE)	277 V / 480 V (3 / N / PE) 240 V / 415 V (3 / N / PE) 230 V / 400 V (3 / N / PE) 220 V / 380 V (3 / N / PE)
Voltage range (Ph-Ph)	305 – 480 V	305 – 480 V
Rated frequency (range)	50 Hz / 60 Hz (42 – 68 Hz)	50 Hz / 60 Hz (42 – 68 Hz)
Rated current	3 x 20.9 A @ 415 V 3 x 21.7 A @ 400 V 3 x 22.8 A @ 380 V	3 x 24.1 A @ 480 V 3 x 27.9 A @ 415 V 3 x 28.9 A @ 400 V 3 x 30.4 A @ 380 V
Max. current	3 x 23.0 A	3 x 31.0 A
Reactive power / cos phi	0 – 100 % Snom / 0.30 ind. – 0.30 cap.	0 – 100 % Snom / 0.30 ind. – 0.30 cap.
Max. total harmonic distortion (THD)	0.7 %	0.5 %
Number of grid phases	3	3
General data		
Max. efficiency	98.0 %	98.4 %
Europ. efficiency	97.6 %	98.1 %
CEC efficiency	97.6 %	98.1 %
Standby consumption	1.5 W	1.5 W
Circuitry topology	transformerless	transformerless
Mechanical data		
Display	graphical display + LEDs	graphical display + LEDs
Control units	4-way navigation + 2 buttons	4-way navigation + 2 buttons
Interfaces	Ethernet, USB, RS485, optional: 4-DI	Ethernet, USB, RS485, optional: 4-DI
Fault signalling relay	potential-free NOC max. 30 V / 1 A	potential-free NOC max. 30 V / 1 A
DC connection	DC plugs (MC4)	DC plugs (MC4)
AC connection	spring-loaded terminal, max. 16 mm <sup>2</sup>	spring-loaded terminal, max. 16 mm <sup>2</sup>
Ambient temperature	-25 °C – +60 °C <sup>1)</sup>	-25 °C – +60 °C <sup>1)</sup>
Humidity	0 – 95 %	0 – 95 %
Max. installation elevation (above MSL)	2 000 m	2 000 m
Min. distance from coast	2 000 m / 500 m (OD+ version)	2 000 m / 500 m (OD+ version)
Cooling	temperature controlled fan	temperature controlled fan
Protection class	IP65	IP65
Noise emission	< 52 db (A)	< 53 db (A)
H x W x D	690 x 420 x 200 mm	690 x 420 x 200 mm
Weight	48 kg	48 kg
Certifications		
Safety	EN 62109-1 / -2, EN 61000-6-1 / -2 / -3, EN 61000-3-2 / -3 / -11 / -12	
Grid connection rule	overview see homepage / download area	

<sup>1)</sup> Power derating at high ambient temperatures

Versions	15.0 TL3	20.0 TL3
DC switch	✓	✓
DC surge protection	○	○
OD+	★	★

standard = ✓ upgradeable = ○ optional = ★